

DATASHEET

Javelin S870-KP

Proximity Card Reader



Proximity access control card reader with keypad for a wide range of security applications

Designed to fit most standard electrical back boxes

Maximum read range of 3" (75mm) dependent on card

Reads 125KHz HID proximity cards

Secure, bi-directional, pseudo-random supervised MCLP communications

Wiegand output

Integrated door pre-held warning buzzer

Multi-tone audio sounder for access granted, denied and PIN prompt

LED feedback for verification of card accepted or rejected

Three color LED alert status indication

Backlight dim energy saving



Product Overview

The Javelin S870-KP is a proximity card reader with keypad for integrated access control. The attractive, contemporary black and silver finish is designed to complement any office or building environment.

The Javelin S870-KP reads I25KHz HID proximity cards.

The Javelin S870-KP is designed for use with the Symmetry range of door controllers and is compatible with all versions of Symmetry software.

The card reader keypad is backlit for ease of use and power saving modes can reduce the lighting level when the card reader is not in use.

The Javelin S870-KP uses secure, bi-directional, pseudorandom supervised MCLP communications to the door controller. Both the card reader and cable are supervised, and an alarm will be generated if the card reader is tampered with, or communications lost.

Wiegand communication is also supported between the card reader and controller.



Javelin S870-KP **Proximity Card Reader**



Specifications

Model Types

• Javelin S870-KP - HID 125KHz proximity card reader with integrated keypad

Dimensions Inches (mm)

- Width = 3.5" (85mm)
- Height = 4.4" (113mm)
- Depth = 0.9" (23mm)

Operating Environment

- -13°F to +158°F (-25°C to +70°C)
- 15% to 90% humidity, non-condensing

Communication Distances

- All Symmetry door controllers to Symmetry S870 (MCLP) = 3000 ft/1000m
- All Symmetry door controllers to Symmetry S870 (Wiegand) = 500 ft/I50m

Power Requirements

- Nominal I2VDC (9-I4V)
- Maximum current consumption I20mA

Purchasing Information

870-KP - keypad proximity reader

Approvals

Radio Regulatory Approvals

- FCC CFR47 Part I5C
- EN 302291

EMC Type Testing

• EN 301489

Access Control Product Testing

- IP44: R & TTE Directive 1999/5/E
- UL 294























DATASHEET

Javelin S870-KP
Proximity Card Reader



















